

# 442 Go-Master® Platinum Diesel Fuel Treatment

**DESCRIPTION:**

Go-Master® Platinum 442 is a diesel fuel treatment built for the delivery of maximum performance year round. It accomplishes this feat by virtually eliminating today's diesel fuel problems. These can include lack of lubricity, high moisture content, high wax content, sulfur, and instability resulting in sludge, gum, carbon, acid and varnish formation.

Some problems occur through venting of outside air and temperature changes, accumulation of water from condensation of water vapor in diesel storage tanks is a constant fight. Without the proper additives, water will collect, over saturate in fuel and accumulate on the bottom of the storage tank. This provides a sanctuary for microbes, corrosion, filter plugging, deterioration of injector nozzles when the fuel is burned, reduced lubricity of fuel, and the potential for fuel-filter icing. Utilizing No. 442 to remove water in stored diesel fuel thus is imperative.

**COMPOSITION:**

442 is made up of unique fuel stabilizers that halt any further breakdown of catalytically cracked fuels and ensure fuel stabilization in all grades of diesel fuel. Superior concentrated icing prevention agents are employed to keep fuel dry and prevent icing caused by harsh cold weather. Upper cylinder, injector and fuel pump lubricants are encompassed to allow for maximum power and performance. 442 contains special additives that neutralize the formation of acids that lead to the development of carbon, gums, varnish and sludge. It contains special rust and corrosion inhibitors along with ingredients that are completely ashless.

**PERFORMANCE CHARACTERISTICS:**

442 is specially formulated for the enhanced performance of diesel fuel, especially where ultra low sulfur diesel (ULSD) fuel is needed.

- Superior H<sub>2</sub>O Dispersion
- Superior Icing Prevention
- Injector Spray Pattern Preservation & Cleaning
- Operational Problem & Maintenance Downtime Reduction
- Superior Cleaning & Lubrication Properties
- Maximum Power & Efficient Combustion
- Rust & Corrosion Prevention
- Upper Cylinder, Injector & Fuel Pump Lubrication
- Neutralizes Harmful Effects of Engine Acids
- Gum & Varnish Prevention
- Ultra Low Sulfur Diesel (ULSD) Compliant

**USES:**

Go-Master® Platinum 442 is designed mainly for problems primarily encountered in diesel fuel; however, it may be used in gasoline when the same benefits are desired.

**DIRECTIONS:**

Usage	Dosage/Directions	Usage Frequency
For Regular Use.	1 quart to 125 gallons (1:500).	Use with every fill up.
For Storage Tank Maintenance Dose.	1 gal to 1500 gallons of fuel. May be used at 1:500 for severe water removal.	
To De-ice or De-gel.	Remove fuel filter; fill new fuel filter with a 50/50 blend of fuel and Go-Master® Platinum 442 and install.	As needed.

The sulfur content of this diesel fuel additive does not exceed 15 ppm. This diesel fuel additive complies with the federal low sulfur content requirements for use in diesel motor vehicles and nonroad engines.

TD 442 (rev. 01/01/2017)