



303 Good Stuff™

White Multi-purpose Grease

DESCRIPTION:

The answer to today's difficult lubrication problems is Good Stuff by Primrose – a white, extremely tacky and adhesive grease designed for the most rigorous operating conditions. Good Stuff is highly waterproof and provides the toughness necessary to protect equipment under extremely heavy loads.

COMPOSITION:

Good Stuff is formulated with Titanex™, and a non-melt thickener system which gives exceptional pumpability and shear stability. In addition, it is empervious to water. Titanex is a non-melt thickener and combined with Equinox™, Good Stuff attains superior oxidation and thermal stability under extremely high temperatures. Extremely high load carrying capacity is achieved with Good Stuff. Good Stuff in combination with Titanex, provides superior protection against shock loading and protects expensive equipment against damaging water.

All the above properties are held together which provides excellent adhesion to metal to resist throw-out. Its excellent tackiness properties also provide great cohesiveness in the lubricant to prevent channeling. Protex is completely shear stable unlike polymer based tackifiers which are found in other greases.

PERFORMANCE CHARACTERISTICS:

Good Stuff will perform in a temperature range of -10°F to 500°F with excellent adherence and shear stability. It will not soften or melt under high temperatures and will not pound out or channel in a bearing. Good Stuff will not allow water to penetrate and will prevent rust or corrosion from occurring. In addition to all this, the extreme pressure protection afforded by Good Stuff's chemistry gives drastically reduced wear from metal-to-metal contact in bearings and equipment. Good Stuff has achieved a 70 pound Timken OK Load Test. The performance characteristics of Good Stuff will allow extended greasing intervals and better equipment protection under the severest conditions in the widest range of applications.

USES:

- Ball Bearings
 Pivot Pins
 Sleeve Bearings
 Hinge Pins
 Journal Bearings
 Universal Joints
- Pillow Blocks
 Ball Joints
 Wheel Bearings
 Slides & Ways
 King Pins

 High Speed Bearings

APPLICATIONS:

Universal Joints
Agricultural
Marine
Automotive
Commercial
Institutional
Mining
Developmental
Logging
Industrial
Municipal
Construction
Fifth Wheels
Amining
Developmental
Logging
Amusement
Drilling
Utilities



303 Good Stuff™ White Multi-purpose Grease

mm²/sec (cSt) Base Oil at 40°

TYPICAL SPECIFICATIONS:

NLGI Grade No. 1 or No. 2 Dropping Point, °F. None Wheel Bearing Leakage Test Pass Oil Separation Excellent Water Resistance Excellent Oxidation Stability psi loss @ 100 hrs. 6 Rust Prevention Test Pass Timken OK Load 70 lbs. Texture Tacky Off White Color

110-160

TD 303 (Rev. 10/25/22) 2