

233 | Odyssey 1300

Synthetic Blend Moly Motor Oil
API SN, SM, SL or SJ SAE 5W-30
API Resource Conserving
ILSAC GF-5

DESCRIPTION:

Odyssey 1300 is a high performance, synthetic blend moly motor oil. Odyssey 1300 gives multigrade performance for all seasons and all temperatures. It meets SN API performance standards for gasoline engines as an SN Resource Conserving motor oil. Odyssey 1300 is highly formulated for superior performance with extended drain intervals.

COMPOSITION:

Odyssey 1300 begins with its special synthetic base stock blend which consists of synthetic hydrocarbon base stocks and polymers blended with ultra-pure, severely hydrocracked base stocks which are refined to an exceptionally high viscosity index. Odyssey 1300 is fully compatible with all other synthetic and conventional mineral oil based motor oils.

Odyssey 1300 is formulated as an extended drain motor oil with its superior additive package. Extensive performance testing has proven exceptional deposit control, thermal stability and elimination of most wear, making much longer drain intervals possible. Highly efficient detergent alkalinity provides super engine cleanliness and spells a dramatic reduction in total maintenance. The superior oxidation and thermal stability of Odyssey 1300, with its highly shear stable viscosity index improvers, prevents oil breakdown, making much longer drain intervals possible. Dramatically reduced oil consumption and increased fuel economy can also be attributed to the use of this high performance product. Outstanding low temperature flow allows for easy starts. Plus it provides for high temperature protection. Wear is essentially eliminated with the addition of our exclusive oil soluble friction modifier, Moly-D.

**PERFORMANCE
CHARACTERISTICS:**

Meets and exceeds the following performance categories and specifications:

API SN, SM, SL, SJ	FIAT – 9.55535-CR-1
API Resource Conserving	Ford – WSS-M2C946-A
ILSAC GF-5	GM – GM 6094M
Chrysler – MS-6395	

USES:

Odyssey 1300 is recommended for use in gasoline engines.

APPLICATIONS:

- Passenger Cars
- 4-Cycle Marine Engines
- Trucks
- Recreational Engines



PRIMROSE PLUS

233 Odyssey 1300 Synthetic Blend Moly Motor Oil, API SN, SM, SL or SJ SAE 5W-30, API Resource Conserving ILSAC GF-5

TYPICAL SPECIFICATIONS:

Product No.	233
SAE Grade	5W-30
Viscosity, cSt @ 100°C	10.2
Viscosity Index	157
Flash Point, °F	> 390
API Gravity	33
Sulfated Ash, % wt	0.9
Base Number (BN)	8.4