

220 Odyssey®

2-Cycle Land & Marine Engine Oil with Fuel Stabilization

DESCRIPTION:

220 Odyssey® is a para-synthetic 2-cycle land and marine engine oil with fuel stabilization, formulated with advanced additive chemistry, which meets and exceeds API TC Lubricity and Pre-Ignition, JASO FD, and ISO-L-EGD performance requirements.

COMPOSITION:

220 Odyssey® is carefully formulated with the finest hand selected base stocks and a fully robust field proven ashless additive package.

PERFORMANCE CHARACTERISTICS:

The following conditions, when combined, are the areas in which 220 Odyssey® is greatly superior to other 2-cycle engine oils on the market today:

- Exhaust Port Blockage Reduction
- Extreme Lubricity Protection
- Superior Detergent Fighting Action
- Contains Piston Antiscuff Additives
- Compatible with E10 Fuel
- Extremely High Viscosity Index
- Reduces Piston Ring Sticking
- Keep Clean and Clean-Up Deposits
- Stabilizes Fuel
- Engine Life Extended
- Extends Plug Life
- Disperses H_oO
- Piston Deposit Reduction
- Low Smoke Formula
- · Reduction in Wear Rates
- Cutting Edge Lubricant Technology

USES:

No. 220, when used as directed, is suitable for use in any land or marine 2-cycle engine, including equipment with Power Valves, and Direct Fuel Injection (DFI).

DIRECTIONS:

Use as directed from your equipment manufacturer; Gasoline Mixing Instructions: 50:1 (2.6 oz. to 1 gallon gasoline); 40:1 (3.2 oz. to 1 gallon gasoline); 16:1 (8 oz. to 1 gallon gasoline); 100:1 (1.3 oz. to 1 gallon gasoline); DFI: pour straight (do not mix) 2-stroke No. 220 oil into DFI container.

TYPICAL SPECIFICATIONS:

Viscosity	SAE 30
Specific Gravity @ 60°F	0.87
Pour Point, °C (°F)	-35 (-31)
Color	Blue

220 TDS New(2/25/2021)